

LIGHTBARS

## BEACONS

**MINIBARS** 

DIRECTIONALS

### WORKLAMPS

# **SIRENS**

SPEAKERS

## **SWITCHES**

AUXILIARY





#### S20IS Siren

Redtronic's S2OIS is an intelligent, user-friendly programmable siren system. The siren system utilises cutting-edge technology to allow the siren to produce any worldwide emergency vehicle warning siren tone within a single device. The S2OIS is innovatively designed to be a durable and flexible product in one, offering IP69K water and dust resistant with its resin sealed inbuilt siren and durable nylon assembly to ensure a fit-and-forget longevity installation whilst being programmable to utilise the many tones built-in for different countries. The S2OIS contains a 20w neodymium speaker and a 20w digital siren offering the same presence as a 100w alternative product, producing 115dB and includes additional features such as Night mode and synchronisation amongst also multiple triggers. The S2OIS is a market leading combination product that is premium of nature but is also affordable and comes with a 2-year warranty.

Part Number S20IS	Voltage 11-16VDC and 20-30 \	<b>Amps</b> /DC 2.4 each	<b>Decibel Outpu</b> 110dB at 3.5m (singl	-	
Features and E Compact all-ir Material: Dura Decibel Outpu Voltage opera Voltage sense Amps/current Impedance: 44 Synchronisati Momentary & 20 watt neody 20 watt digita EMC / R10 cor KBA approved IP69K protect 3 positive or r Latching tone Audible sense	<ul> <li>Features and Benefits</li> <li>Compact all-in-one cutting-edge technology speaker siren</li> <li>Material: Durable nylon assembly with inbuilt resin sealed siren</li> <li>Decibel Output: 110dB at 3.5m (Single Unit)</li> <li>Voltage operation: 11-16 VDC and 20-30 VDC</li> <li>Voltage sense: 9.5VDC de-power</li> <li>Amps/current peak max: 2.4 amps each [4.8amps in total]</li> <li>Impedance: 4ohm</li> <li>Synchronisation with other S20IS Redtronic products</li> <li>Momentary &amp; latching switch functions</li> <li>20 watt neodymium speaker (per unit)</li> <li>20 watt digital siren (per unit)</li> <li>EMC / R10 compliant</li> <li>KBA approved tones</li> <li>JP69K protection against dust &amp; water ingress</li> <li>3 positive or negative triggers (tone 1 - city, tone 2 - country, tone 3 - compressor)</li> <li>Latching tones</li> <li>Audible sense / monitor output</li> </ul>				
• Warranty: 2 ye	94	112 24,24 98 98 98 98 98 98 98 98 98 98	ALTERNATIVI MOUNTING POSITION		