







## Frequently Asked Questions

- Q: What factors affect the solar energy conversion rate?
- 1. The intensity of the sunlight
- Ambient temperature
   the angle at which the solar panel is placed
- 4. the length of the solar cable
- Q: Can solar charging panels be waterproof?

Solar panels are dustproof, waterproof, durable, and suitable for outdoor scenes. If you need to clean the solar panels, durable running water drenching, avoid using high-pressure water force (such as sprinklers).

Pressure may make the solar panels damaged (to extend the life of solar panels, please do not immerse them in water)

-3-

or parallel, make sure that the maximum cumulative voltage and current of the solar panels do not exceed the maximum voltage and current of the

Q: How many solar panels can be used for one outdoor power supply?

outdoor power supply Q: Can solar panel be used in extreme weather?

1. Check the maximum open-circuit voltage

Maximum short-circuit current

series or parallel

The solar panel is used in stable weather conditions as much as possible.

-4°F to 185°F (-20°C to 85°C) during regular use and storage temperatures.

Avoid use in adverse conditions such as thunderstorms, high winds, hail, etc.

3. the maximum power of solar panels when using multiple solar panels in

Maximum power of solar panels When using multiple solar panels in series

Q: Can energy be stored inside the solar panel?

The solar panel converts solar energy into electrical energy and transmits the electrical energy in the form of direct current to products such as outdoor power supplies. The solar panel does not store electrical energy on its own.

- Do not bend the solar panel (angle > 30)
- Do not immerse the solar panel in water or any other liquid
- Do not use solar panels near fire or heaters
- Do not hang the solar panel with sharp objects
- Do not remove the solar panel by yourself
- Do not place corrosive substances on the solar panel

recn	Sped	ဌ
------	------	---

Power Rating	100W ± 5%
Open Circuit Voltage	24V(Not less than:22.8V)
Short Circuit Current	6A(Not less than:5.7A)
Working Voltage	20V(Not less than: 19.6V)
Operating Current	5A, (Not less than: 4.9A)
Conversion Efficiency	≥24%
Battery Type	Monocrystalline silicon
Interface Type	Xt60
Use and Storage Temperature	-4°F to 185°F (-20°C to 85°C)
Weight	3.6±0.2kg
Expanded Size	536*1228*25mm
Folded Size	536*608*38mm

-5-

-4-