

Beacon

ECO

MEGA-FLASH

Dual Voltage
11 - 30 volts

Colours
● ● ● ● ● ● ● ● ● ●



ORDER CODE	FIXING METHOD	MM (DxH)	LED	IP RATING	WARRANTY	ADDITIONAL INFORMATION
EM190	3 Point Screw	130mm X 118mm	3	IP65	2 YEARS	The ECO beacon is a low-cost option for customers on a budget. Available in 5 fixing methods: 3 point screw, single bolt, mag mount, pole mount and din mount. Only available in single colour options.
EM191	Mag Mount	130mm X 126mm	3	IP65	2 YEARS	
EM192	Single Bolt	130mm X 118mm	3	IP65	2 YEARS	
EM193	Pole Mount	130mm X 708mm (Min) 130mm X 1588mm (Max)	3	IP65	2 YEARS	
EM194	Din Mount	130mm X 178mm	3	IP65	2 YEARS	

Tornado (Low-Profile)

Fx Technology

MEGA-FLASH

ECE R65
Approved

Dual Voltage
11 - 30 volts

Colours
● ● ● ● ● ● ● ● ● ●

TORNADO
LED BEACON



NEW
DIN MOUNT

DEKRA
SPEED TEST - APPROVED
147mph (237kph)



ORDER CODE	FIXING METHOD	MM (DxH)	LED	IP RATING	WARRANTY	ADDITIONAL INFORMATION
EM400**	Single Bolt	150mm X 45mm	12 (Single Colour)	IP66	5 YEARS	The TORNADO beacon is recognised as one of the brightest and lowest profile beacons available. Standard features include pattern select, dim facility and synchronisation.
EM401**	Mag Mount	150mm X 54mm	12 (Single Colour)	IP66	5 YEARS	
EM402**	Suction Mount	150mm X 101mm	12 (Single Colour)	IP66	5 YEARS	
EM403**	Pole Mount	150mm X 635mm (Min) 150mm X 1515mm (Max)	12 (Single Colour)	IP66	5 YEARS	
EM404**	Din Mount	150mm X 105mm	12 (Single Colour)	IP66	5 YEARS	
EM4002****	Single Bolt	150mm X 45mm	24 (Dual Colour)	IP66	5 YEARS	The TORNADO beacon is also available in dual colour. Each colour can be operated independently.
EM4012****	Mag Mount	150mm X 54mm	24 (Dual Colour)	IP66	5 YEARS	
EM4022****	Suction Mount	150mm X 101mm	24 (Dual Colour)	IP66	5 YEARS	
EM4032****	Pole Mount	150mm X 635mm (Min) 150mm X 1515mm (Max)	24 (Dual Colour)	IP66	5 YEARS	

ECE R65
Approved

Dual Voltage
11 - 30 volts

Colours
● ● ● ● ●

TORNADO
LED BEACON



ORDER CODE	FIXING METHOD	MM (DxH)	LED	IP RATING	WARRANTY	ADDITIONAL INFORMATION
EM410D**	Single Bolt	150mm X 75mm	24 (Single Colour)	IP66	5 YEARS	The Double-Stack Tornado beacon provides 360 degree light output including a variety of lens colour options.
EM411D**	Mag Mount	150mm X 82mm	24 (Single Colour)	IP66	5 YEARS	
EM412D**	Suction Mount	150mm X 131mm	24 (Single Colour)	IP66	5 YEARS	
EM413D**	Pole Mount	150mm X 665mm (Min) 150mm X 1545mm (Max)	24 (Single Colour)	IP66	5 YEARS	
EM414D**	Din Mount	150mm X 135mm	24 (Single Colour)	IP66	5 YEARS	The dual colour version offers flexibility for those users who require more than one warning colour.
EM410D2****	Single Bolt	150mm X 75mm	48 (Dual Colour)	IP66	5 YEARS	
EM411D2****	Mag Mount	150mm X 82mm	48 (Dual Colour)	IP66	5 YEARS	
EM412D2****	Suction Mount	150mm X 131mm	48 (Dual Colour)	IP66	5 YEARS	
EM413D2****	Pole Mount	150mm X 665mm (Min) 150mm X 1545mm (Max)	48 (Dual Colour)	IP66	5 YEARS	

Low-Profile Tornado

Fixing Methods



Double-Stack Tornado

Fixing Methods

