

CAMERA SPECIFICATION

Image Device	1/2.9" CMOS		
Effective Pixels	1920 (H) x 1080 (V)		
S/N Ratio	38		
White Balance	Auto		
BLC	Auto		
Dynamic Range	81dB		
Operation Frequency:	2403MHz-2478MHz		
Transmission Distance (Barrier Free):	FCC: 300m	CE: 200m	MIC: 60m
Receiving Sensitivity:	-78dBm		
Video Codec:	H.264		
Transmission Power:	FCC: ≤26dBm	CE: ≤20dBm	MIC: ≤10dBm
Modulation:	FHSS		
Delay:	Wireless Monitor: 130ms Wireless Receiver: 170ms		
RF Bit Rate:	12Mbps		
Operating Temperature	-20℃ ~ 70℃, RH95%MAX.		
Storage Temperature	-30℃ ~ 80℃, RH95%MAX.		
Minimum Illumination	☒ 0Lux ☐ 0.1Lux		
Power Supply	DC10-32V		
Power Consumption	Day: 1.8W-2.5W		Night: 3.6W-4.3W
Night Vision Distance	☐ NO IR LED ☐ 8~10m ☒ 12~15m ☐ 20~25m		
Waterproof Rating	IP69K		
Audio	☒ Yes ☐ No		
Viewing Angle	☐ 35° ☐ 50° ☐ 70° ☐ 100° ☒ 130° ☐ 150° ☐ 170°		
Heater	☐ Yes ☒ No		
IR-Cut	☒ Yes ☐ No		